



Overturning the traditional, one more choice

Integration of Innovation and Technology

The new integrated LED T8 Fixture, innovation for new technological products, subvert the traditional technologies and applications, achieve the perfect fit of the lamp and lamp holder, bring easier, more efficient solutions to home and office decoration.



Safe material

The integrated main body uses fire protection of engineering design, double insulated wires, no leakage risk, safe and secure.




Light-weighted easy installation

Lighthouse is very lightweight, it has a variety of installation methods such as ceiling and hanging to meet different use of the environment, creating a lower installation and maintenance costs.



Long life

Has excellent low temperature start-up performance, lamp life up to 36,000 hours, much higher than traditional T8 fixture 4 times.



Super brightness of glow effect

CRI \geq 80Ra, comfortable light color creates better atmosphere.



Perfectly substitute for traditional

New type of lamp holder with elegant appearance, without mercury, effect of energy saving is double than traditional lamp, more suitable for environment matching.



Product of A+ energy efficiency



L1200*W74.5*H23mm



| BarCode | CCT | Light Color | Brightness | Power | EEl | Incandescent Lamp Power |
|---------|-------|---------------|------------|-------|-----|-------------------------|
| 001956 | 3000K | Warm light | 2900lumen | 36W | A+ | 290W |
| 001963 | 6000K | Day Light | 3000lumen | 36W | A+ | 300W |
| 002694 | 4000K | Natural White | 2900lm | 36W | A+ | 290W |

Protection : IP20

CRI : $\geq 80Ra$

PF : > 0.9

Life span : 35000Hours

Beam angle : 120°

Hg% : $< 0.1\%$



L1500*W74*H23mm



| BarCode | CCT | Light Color | Brightness | Power | EEl | Incandescent Lamp Power |
|---------|-------|---------------|------------|-------|-----|-------------------------|
| 004902 | 4000K | Natural White | 4150lm | 50W | A+ | 400W |
| 004919 | 6000K | Day Light | 4150lm | 50W | A+ | 400W |

Protection : IP20

CRI : $\geq 80Ra$

PF : > 0.9

Life span : 35000Hours

Beam angle : 120°

Hg% : $< 0.1\%$



L1200*W53*H28mm



| BarCode | CCT | Light Color | Brightness | Power | EEl | Incandescent Lamp Power |
|---------|-------|-------------|------------|-------|-----|-------------------------|
| 001970 | 3000K | Warm light | 2900lumen | 36W | A+ | 290W |
| 001987 | 6000K | Day Light | 3000lumen | 36W | A+ | 300W |

Protection : IP65

CRI : $\geq 80Ra$

PF : > 0.9

Life span : 35000Hours

Beam angle : 120°

Hg% : $< 0.1\%$